



JS6000BX/GX

PRESSURE WASHER
420 BAR/6100 PSI

RECOMMENDED FOR:

Hot Water Pressure Washer Machines.

DO NOT USE with Steam.

PERFORMANCE:

Meets or Exceeds the Performance Requirements of:
EN 1829-2.

TUBE:

Black, heat resistant synthetic rubber.

REINFORCEMENT:

Two braid of high tensile steel wire.

COVER:

Oil resistant synthetic rubber formulated to resist marking.

JS6000BX, blue, highly abrasion resistant (AR), non marking.

JS6000GX, grey, highly abrasion resistant (AR), non marking.

Embossed layline for positive, permanent identification.

No skiving required for T2000 Series Crimp Couplings.

TEMPERATURE RANGE:

JS6000BX/GX JETSTORM Hoses handle hot water up to
+135°C (+275°F) with intermittent service to
+150°C (+302°F).

WORKING PRESSURE:

Maximum working pressures are based on 3:1 safety factor
(maximum working pressure to minimum burst pressure).

COUPLINGS:

NON-SKIVE ONE-PIECE CRIMP

T2000 Series (sizes -04 to -08) pages 187 to 232.
Assembly Instructions pages 478.

A MEMBER OF

THE WATERJET TECHNOLOGY ASSOCIATION (WJTA) AND
INDUSTRIAL & MUNICIPAL CLEANING ASSOCIATION (IMCA)

THE AUSTRALASIAN HIGH PRESSURE WATER JETTING
ASSOCIATION

JS6000 JETSTORM - PRESSURE WASHER HOSE															
PART NO	HOSE SIZE	NOMINAL HOSE ID		NOMINAL HOSE OD		MAXIMUM WORKING PRESSURE		MINIMUM BURST PRESSURE		MINIMUM BEND RADIUS		AVERAGE WEIGHT		ONE PIECE	
Hose	DN	Dash	mm	inch	mm	inch	bar	psi	bar	psi	mm	inch	kg/m	lb/ft	NON-SKIVE
JS6004BX	6	-04	6,6	1/4	13,5	0.53	420	6100	1260	18300	50	2.0	0,26	0.17	T2000
JS6005BX	8	-05	8,2	5/16	15,6	0.61	420	6100	1260	18300	55	2.2	0,34	0.23	T2000
JS6006BX	10	-06	9,8	3/8	17,4	0.69	420	6100	1260	18300	65	2.6	0,35	0.24	T2000
JS6008BX	12	-08	13,0	1/2	20,4	0.80	420	6100	1260	18300	90	3.6	0,49	0.33	T2000
JS6004GX	6	-04	6,6	1/4	13,5	0.53	420	6100	1260	18300	50	2.0	0,26	0.17	T2000
JS6005GX	8	-05	8,2	5/16	15,6	0.61	420	6100	1260	18300	55	2.2	0,34	0.23	T2000
JS6006GX	10	-06	9,8	3/8	17,4	0.69	420	6100	1260	18300	65	2.6	0,35	0.24	T2000
JS6008GX	12	-08	13,0	1/2	20,4	0.80	420	6100	1260	18300	90	3.6	0,49	0.33	T2000

Cutting and Assembly Charges apply to all RYCO industrial hoses, and vary by hose types and sizes. Contact RYCO for additional information or visit www.RYCO.com.au